



BIBD2/08, Double Sided Eight Conductor Clear Insulated Multi-Tap Connector

By Burndy
Catalog # BIBD2/08



Aluminum Multiple Tap Connector, Clear Insulated, 8 Port, 2 Sided Entry, 14-2/0 Awg, Al/Cu Rated

Features

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

Application

For Indoor Use Only, Copper Or Stranded Aluminum

General

| | |
|---------------------------------------|------------------|
| Catalog Number | BIBD2/08 |
| Connector Type | Multi Tap |
| EU RoHS Indicator | Yes |
| Hex Key | 3/16 |
| Insulation | Y |
| Insulation Type | Plastisol |
| Material | Aluminum |
| Material - Hardware | Aluminum |
| Number Of Ports | 8 |
| Physical Attribute - Number of Screws | 8 |
| Physical Attribute - Screw Type | Allen |
| Plated | N |
| Plating Type | Unplated |
| Sub Brand | UNITAP |
| Temperature Rating | 194 |
| Trade Name | UNITAP™ |
| Type | BIBD, Multi-Port |
| UPC | 781810223987 |
| UPC 12 Digit | 7818102239877 |

Dimensions

| | |
|---------------------------------|------------|
| Dimension - Height fraction | 1.375 in |
| Dimension - Height inch | 1.38 in |
| Dimension - L Length Overall mm | 141 mm |
| Dimension - Length Overall inch | 5.55 in |
| Dimension - Width fraction | 1-14/25 in |
| Dimension - Width inch | 1.56 in |
| Dimension - Width mm | 40 mm |

Electrical Ratings

| | |
|-------------------|-------|
| Voltage - Maximum | 600 V |
|-------------------|-------|

Conductor Related

| | |
|-----------------------------------|---|
| Conductor - AL Str Size | 8 AWG;6 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG |
| Conductor - AL Str Size Range | 8 AWG-2/0 AWG |
| Conductor - Copper Str Size | 14 AWG;12 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 Str |
| Conductor - Copper Str Size Range | 14 AWG - 2/0 AWG |
| Conductor Size | 14-2/0 AWG |
| Conductor Type | <ul style="list-style-type: none">• AL C Str-Size• CU C Str-Size |

Certifications And Compliance

| | |
|---|--------------|
| Buy American Compliant | Yes |
| Certification - CSA Approved | Yes |
| Certification - ETL | No |
| Certification - UL Listed Direct Burial | No |
| Certification - UL Recognized | No |
| Certification - cULus | No |
| Industry Standard(s) | UL 486A-486B |
| Standards - Industry Standards Met | UL 486A-486B |
| Standards - RoHS Compliance Status | CM |
| UL Listed | Yes |

Logistics

Minimum Pack Quantity 1

Product Assets

[Catalogs - UNITAP™ Products](#)
[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
[Catalogs - BURNDY Master Catalog - Section A - Mechanical](#)
[Customer Notices - Prop 65 Notice](#)
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
[Product Cross Section Image\(s\) - BUR_BIBD_Lineart](#)
[Sales Drawings - sc210991-05](#)
[Specifications - BURNDY_BIBD208_Specsheet](#)
[Specifications - BIBD2/08](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
BRDY-BIBD208-SPEC-EN | REV 8/2024