



BTCGC250SS, Aluminum Ground Tray Clamp, #6-250 kcmil

By Burndy
Catalog # BTCGC250SS

Aluminum ground tray clamp, accomodates ground wire size #6 to 250 Kcmil



Features

- Tin plated aluminum for durable, long lasting corrosion resistance
- cULus 467 Listed for Grounding and Bonding in US and Canada
- cULus 2703 Listed for solar PV applications in US and Canada
- Accommodates most popular styles of cable tray with inside or outside flange
- Quick and easy installation
- no drilling or special tools required
- Set screw bonds clamp to the cable tray while another set screw securely fastens the grounding conductor to the clamp providing vibration resistance and outstanding pull-out values
- Grounding green hardware as required in Section 8.4 of UL2703

Application

Type BTCGC-SS clamps are suitable for outdoor applications and may be used with most types of cable tray with an inside or outside flange design

General

Allen Key Size	1/4 in
Catalog Number	BTCGC250SS
EU RoHS Indicator	Contact Manufacturer
Finish Type	Tin Plated
Material	Aluminum
Material - Hardware	Stainless steel
UPC	621945505957

Dimensions

Dimensions	2.25 in x 0.88 in x 2.43 in
Height	2.43 in
Length	2.25 in
Thickness - Flange Plate	1/2 in
Width	0.88 in

Conductor Related

Conductor - AL Str Size Range	#6 AWG - 250 Kcmil
Conductor - Copper Str Size Range	6 AWG - 250 kcmil
Conductor Range	#6 AWG - 250 Kcmil AL-CU

Certifications And Compliance

Buy American Compliant Certified Listed	Contact Manufacturer cULus Listed
---	-----------------------------------

Product Assets

[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
[Catalogs - BURNDY Master Catalog - Section E2 - Mechanical Grounding](#)
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
[Sales Drawings - 50087187](#)
[Specifications - BTCGC250SS](#)