



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

FQN18M25X03D  
 7818102930033  
 MALEDISC 22-18AWG-FI NYL  
 Active

**Web Use**  
 BURNDY Product Line

Dimensional	
Width (in)	0.25
Strip Length	3/8"
Length (in)	0.99
F - Spacing (in) (Width - Center to Center)	0.06
Thickness	0.03
Diameter (in) - Total	0.80
Electrical	
Max Voltage Rating	300
General	
Product Description	Brass Fully Insul Male Quick Disconnects, Funnel Entry, 10-12 AWG, 300 V, 0.96" L, 0.25" W, Nylon Insul, Tin Plated, Red(Insul Color)
Other	
Bulk Package	FQN18M25X03B
Physical	
Type of Plating	Tin
Connector Type	Male Disconnect
Insulation Type	Nylon
Plated (Yes or No)	Y
Approvals / Certifications	
UL Listed	N
CSA Certified	N
ROHS Compatible	Compliant
UL Recognized	N
CULUS	Y
Industry Standards	UL467
Conductor(s)	
Copper Solid Size (Range)	N/A
Copper Stranded (Range)	20 AWG-18 AWG
Documentation	

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175