



# HSB200T48PF, Heat Shrink Tubing, 2.00" ID Min.(Exp.), 1.00" ID Max. (Rec.), 250- 500, Polyolefin, Thin Wall, Black, Shrink ratio-2:1, 600V.



By Burndy  
Catalog # [HSB200T48PF](#)

Heat Shrink Tubing, 2.00" ID Min.(Exp.), 1.00" ID Max.(Rec.), 250-500, Polyolefin, Thin Wall, Black, Shrink ratio-2:1, 600V.

### Features

- Heat Shrink Tubing, 2.00" ID Min (Exp), 1.00" ID Max (Rec)
- 250-500, Polyolefin, Thin Wall, Black
- Shrink Ratio 2:1, 600 V

### General

Catalog Number	HSB200T48PF
Connector Type	THIN WALL REEL
Material	Cross-linked Polyolefin
UPC	781810213032

### Conductor Related

Conductor Range	250-500 Kcmil
Conductor Size	350kcmil - 750kcmil

### Certifications And Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Standards - RoHS Compliance Status	CM
UL Listed	No

### Logistics

Minimum Pack Quantity	1
-----------------------	---

### Product Assets

- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Literature - Polyolefin Thin Wall Heat Shrink Cross Reference Guide](#)
- [Product Cross Section Image\(s\) - BUR\\_HSB38T300PF\\_LineArt](#)
- [Sales Drawings - SD211941](#)
- [Specifications - HSB200T48PF](#)