



BURNDY Catalog Number
UPC Number
Description
Status

HSIC200FR
7818102665333
5/PK, 300-1750, HVYWALL
Active

Web Use
BURNDY Product Line

Dimensional

Wall Thickness - Recovery	0.160
Flex Wire Range	250-1111 kcmil
Dimension (Max Before Shrink)	2.00
Expansion Length	4.5
Length - Recovery	3.50
Wall Thickness - Exp	0.050
Recovery - Max ID	0.63

General

Product Description

Heat Shrinkable End Cap, 2" ID
Min.(Exp.), 0.63" ID Max.(Rec.),
250-1111 Flex, Cross Linked
Polyolefin, Heavy Wall, Flame
Retardant, Black, 600V

Approvals / Certifications

UL Listed	Y
CSA Certified	N
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

Physical

Shrink Ratio	3:1
Color	Black
Code Wire Range	300-1750 kcmil

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175