



## K11A36U2N, 1/2" diameter stud holes spaced 1-3/4" on center (NEMA-spacing), 600 Volt Rated, Aluminum, Tin plated

By Burndy  
Catalog # K11A36U2N

1/2" diameter stud holes spaced 1-3/4" on center (NEMA-spacing), 600 Volt Rated, Aluminum, Tin plated.

### Features

- AL9CU Dual Rated for both copper and aluminum conductor
- Listed to UL Wire Connector Standard UL486A-486B
- 1/2" diameter stud holes spaced 1-3/4" on center (NEMA-spacing)
- 600 Volt Rated
- Range Taking conductor port

### Application

Terminate multiple conductors onto equipment pads, panel boards, or switchgear

### General

Catalog Number	K11A36U2N
Connector Type	Stacked
Construction Material - Main	Aluminum
EU RoHS Indicator	Contact Manufacturer
Finish Type	Tin-Plated
Insulation	N
Material	Aluminum
Sub Brand	Terminal
Type	K-A-U2N
UPC	781810670149



### Dimensions

Dimension - Bolt Size fraction	1/2
Dimensions	5.34 in x 1.50 in x 3.00 in
Height	3 in
Length	5.34 in
Width	1.5 in

### Conductor Related

Conductor Size	2 AWG-600 KCMIL
----------------	-----------------

### Certifications And Compliance

Buy American Compliant	Contact Manufacturer
Certification - CSA Approved	Yes

### Logistics

Minimum Pack Quantity	1
-----------------------	---

### Product Assets

[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)  
[Catalogs - BURNDY Master Catalog - Section A - Mechanical](#)  
[Customer Notices - Prop 65 Notice](#)  
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)  
[Sales Drawings - 50094864](#)  
[Specifications - K11A36U2N](#)