



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

QN14F18X02D  
 7818102934099  
 FEM DISC 16-14 AWG-NYLON  
 Active

**Web Use**  
 BURNDY Product Line

**Dimensional**

Tab Size .187 X .020  
 Strip Length 3/8"  
 Width (in) 0.19  
 Length (in) 0.82  
 F - Spacing (in) (Width - Center to Center) 0.08  
 B Length (in) 0.23

**General**

**Product Description** Brass Female Quick Disconnect, 16-14 AWG, Nylon Insulated, Funnel Entry, Tin Plated

**Other**

**Bulk Package** QN14F18X02B

**Approvals / Certifications**

UL Listed N  
 CSA Certified N  
 ROHS Compatible Compliant  
 UL Recognized N  
 CULUS Y  
 Industry Standards UL467

**Conductor(s)**

Copper Solid Size (Range) N/A  
 Copper Stranded (Range) 16 AWG-14 AWG

**Physical**

Type of Plating Tin  
 Connector Type Female Disconnect  
 Insulation Type Nylon  
 Plated (Yes or No) Y

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175