



## QPX3428

by Burndy  
Catalog ID: QPX3428

Prop 65 Notice

Parallel Clamp, Copper: 250-500 kcmil (Run)/ 1-4/0 AWG (Tap).

Features: The VERSITAP Type QPX Is Recommended For Tee, Cross, Parallel, Butt And Tap Connections, Range-Taking, Only 10 Connectors Required To Accommodate Conductor Sizes From #6 Stranded To 1000 KCMIL, Edges Are Rounded For Easy Taping, Made Of High Strength, High Conductivity Copper Alloy And Silicone Bronze DURIUM Hardware, Conductor Type: Run And Tap: Copperweld - Copper, Copperweld, Commercial Stranded Copper, Stud/bolt Size: 3/8 IN, Length: 1-3/4 IN, Installation Torque: 300 IN-LB, Width: 2 IN, Height: 2-1/2 IN

## Product Details

### General

Application	For Tee, Cross, Parallel, Butt And Tap Connections, Copper, Copperweld And Copperweld-Copper
Installation Torque Recommended in-lb	240 LBS/in
Material	Copper
Material - Hardware	DURIUM™ Silicon Bronze
Physical Attribute - Number of Screws	2
Physical Attribute - Screw Type	Hexagonal Bolt
Plated	N
Plating Type	Unplated
Sub Brand	VERSITAP
Temperature Rating	194
Trade Name	VERSITAP™
Type	QPX
UPC	781810343258
UPC 12 Digit	7818103432588

### Dimensions

Dimension - Height fraction	2-3/4
Dimension - Height inch	2.75
Dimension - L Length Overall mm	44 mm
Dimension - Length Overall inch	1.75 in
Dimension - Width fraction	2-1/16 in
Dimension - Width inch	2.06
Dimension - Width mm	52 mm

### Electrical Ratings

Rating - Minimum Voltage	600
--------------------------	-----

### Conductor Related

Conductor - Copper Str Run	250 kcmil;300 kcmil;350 kcmil;400 kcmil;450 kcmil;500 kcmil
----------------------------	---

Conductor - Copper Str Run Range	250 kcmil-500 kcmil
Conductor - Copper Str Tap	1 AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Str Tap Range	1 AWG-4/0 AWG
Conductor - CopperWeld Solid Run	9 AWG;8 AWG;7 AWG;6 AWG
Conductor - CopperWeld Solid Run Range	9 AWG-6 AWG
Conductor - CopperWeld Solid Tap	9 AWG;8 AWG;7 AWG;6 AWG;5 AWG
Conductor - CopperWeld Solid Tap Range	9 AWG-5 AWG
Conductor - CopperWeld Str Run	4/0 EK AWG
Conductor - CopperWeld Str Run Range	4/0 EK AWG
Conductor - CopperWeld Str Tap	3 A AWG;3 J AWG;3 K AWG;3 N AWG;3 P AWG;2 A AWG;2 F AWG;2 G AWG;2 J AWG;2 K AWG;2 N AWG;2 P AWG;1 F AWG;1 G AWG;1 J AWG;1 K AWG;1 N AWG;1/0 F AWG;1/0 G AWG;1/0 J AWG;1/0 K AWG;2/0 F AWG;2/0 G AWG;2/0 J AWG;2/0 K AWG;2/0 V AWG;3/0 E AWG;3/0 EK AWG;3/0 F AWG;3/0 G AWG;3/0 J AWG;3/0 V AWG
Conductor - CopperWeld Str Tap Range	3 A AWG-3/0 V AWG
Conductor Type	<ul style="list-style-type: none"> <li>• CU C Str-Run</li> <li>• CU Weld C Str-Run</li> <li>• CU Weld C Solid-Run</li> <li>• CU C Str-Tap</li> <li>• CU Weld C Str-Tap</li> <li>• CU Weld C Solid-Tap</li> </ul>

## Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct Burial	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL486C
Standards - Industry Standards Met	UL486C
Standards - RoHS Compliance Status	EX
UL Listed	Yes

## Logistics

Minimum Pack Quantity	1
-----------------------	---

## For further technical assistance, please contact us

**BURNDY Headquarters**  
47 East Industrial Park Drive  
Manchester, New Hampshire 03109

**Customer Service Hours:**  
8 AM - 8 PM Eastern Monday-Friday  
Emergency Service 24-hours/365 Days  
Phone: 1-800-346-4175  
1-603-647-5299 (International)