



YSR4CFX8CFXLTCKITC, Cu Splice Reducer with Clear Heat Shrink,

By Burndy
Catalog # YSR4CFX8CFXLTCKITC

CU Splice Reducer, Barrel A 4 Flex G,H,I,K,M,DLO, 4 AWG, Barrel B 8 Flex G,H,I,K,M,DLO, 8 AWG, Standard Barrel, Internal Chamfer, Tin Plated, Connector is UL/CSA, 90°C Up to 35kV, Kit comes with Clear Heat Shrink, Gray/Red Color Code, 8/49 Die Index.



Application

Wire Reducing Splice

General

Catalog Number	YSR4CFX8CFXLTCKITC
Color Code	Gray, Red
Color Code - Side A	Gray
Color Code - Side B	Red
Connector Type	STANDARD BARREL KITS
Construction Material - Main	Copper
Die Index	8/49
Die Index - Element A	8
Die Index - Element B	49
Die Index Run Side	8
Die Index Tap Side	49
EU RoHS Indicator	Contact Manufacturer
Feature - Barrel Style	Skived
Feature - Barrel Type	Standard
Finish Type	Tin-Plated
Material	COPPER
Plated	Y
Plating Type	Tin - Electro Plated
Sub Brand	HYREDUCER
Temperature Rating	194
Trade Name	HYREDUCER™
Type	YSR-TC
UPC	781810473931
UPC 12 Digit	7818104739311

Electrical Ratings

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - B Length fraction	3/4 in
Dimension - B Length inch	0.74 in
Dimension - L Length Overall mm	38 mm
Dimension - Length BB inch	0.60 in
Dimension - Length Overall inch	1.50 in
Dimension - Strip Length inch	0.71 in

Conductor Related

Conductor - Copper DLO Size 4 AWG Range

Conductor - Copper Flex G Run 4 AWG

Conductor - Copper Flex G Size 4 AWG A

Conductor - Copper Flex G Size 4 AWG A Range

Conductor - Copper Flex G Size 8 AWG B

Conductor - Copper Flex G Size 8 AWG B Range

Conductor - Copper Flex G Size 4 AWG Range

Conductor - Copper Flex G Tap 8 AWG

Conductor - Copper Flex H Run 4 AWG

Conductor - Copper Flex H Size 4 AWG A

Conductor - Copper Flex H Size 4 AWG A Range

Conductor - Copper Flex H Size 8 AWG B

Conductor - Copper Flex H Size 8 AWG B Range

Conductor - Copper Flex H Size 4 AWG Range

Conductor - Copper Flex H Tap 8 AWG

Conductor - Copper Flex I Run 4 AWG

Conductor - Copper Flex I Size 4 AWG A

Conductor - Copper Flex I Size 4 AWG A Range

Conductor - Copper Flex I Size 8 AWG B

Conductor - Copper Flex I Size 8 AWG B Range

Conductor - Copper Flex I Size 4 AWG Range

Conductor - Copper Flex I Tap 8 AWG

Conductor - Copper Flex K Run 4 AWG

Conductor - Copper Flex K Size 4 AWG A

Conductor - Copper Flex K Size 4 AWG A Range

Conductor - Copper Flex K Size 8 AWG B

Conductor - Copper Flex K Size 8 AWG B Range

Conductor - Copper Flex K Size 4 AWG Range

Conductor - Copper Flex K Tap 8 AWG

Conductor - Copper Flex M Run 4 AWG

Conductor - Copper Flex M Size A 4 AWG

Conductor - Copper Flex M Size A Range 4 AWG

Conductor - Copper Flex M Size B 8 AWG

Conductor - Copper Flex M Size B Range 8 AWG

Conductor - Copper Flex M Tap 8 AWG

Conductor - Copper Solid Size 6 AWG B

Conductor - Copper Str Run 4 AWG Range

Conductor - Copper Str Size 4 AWG-8 AWG

Conductor - Copper Str Size B 8 AWG

Conductor - Copper Str Tap 6 AWG Range

Conductor - Material COPPER

Conductor Size 4 AWG-8 AWG

Conductor Type CODE/FLEX

Wire Size 4 AWG-8 AWG

Certifications And Compliance

Buy American Compliant Contact Manufacturer

Certification - CSA Approved No

Certification - ETL No

Certification - UL Recognized No

Certification - cULus No

Standards - RoHS Compliance CM

Status

UL Listed No

Logistics

Carton Quantity 25

Minimum Pack Quantity 1

Pallet Quantity 6000

Product Assets

[3D Models - YSR4CFX8CFXLTCKITC_MODEL-PDF](#)

[3D Models - YSR4CFX8CFXLTCKITC_MODEL-IGES](#)

[3D Models - YSR4CFX8CFXLTCKITC_MODEL-STEP](#)

[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)

[Catalogs - BURNDY Master Catalog - Section C - Compression Connections](#)

[Customer Notices - Prop 65 Notice](#)

[Installation Manuals - SPLICE KIT trilingual](#)

[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)

[Sales Drawings - 10021428](#)

[Specifications - YSR4CFX8CFXLTCKITC](#)



A Hubbell brand