

Specifications



Eaton JM60060-3MW24

Eaton Bussmann series JM modular fuse block, 60 A, 3P, 120°C, Class J, CVR(I)-J-60060, Black, Box lug, 200 kA, 75°C, Panel, DIN rail, 600 V, Line: (2) #10 AWG Cu, Load: #8-16 AWG Cu, Line: #6 AWG Cu, Load: (2)#12-16 AWG Cu

General specifications

PRODUCT NAME	Eaton Bussmann series JM modular fuse block
CATALOG NUMBER	JM60060-3MW24
UPC	051712620703
PRODUCT LENGTH/DEPTH	3.7 in
PRODUCT HEIGHT	2.6 in
PRODUCT WIDTH	4.5 in
PRODUCT WEIGHT	0.73625 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	ARO European Pressure Equipment Directive (PED) 97 /23 EC



Powering Business Worldwide

Electrical rating

AMPERAGE RATING	60 A
IMPULSE WITHSTAND VOLTAGE	200 kA RMS symmetrical
INTERRUPT RATING	200 kAIC
SHORT-CIRCUIT RATING	200 kA RMS symmetrical
TORQUE RATING	50 lb-in maximum
VOLTAGE RATING	600 V

General information

ACCESSORIES	CVR(I)-J-60060
CONNECTION	Box lug
MOUNTING METHOD	DIN rail Panel
SPECIAL FEATURES	Multi-Wire Line-Side & Load-Side Lugs

Physical details

COLOR	Black
CONDUCTOR MATERIAL RATED FOR	Both
CONDUCTOR TEMPERATURE RATING	75 °C
CONDUCTOR TYPE	Stranded
FUSE TYPE	Class J
NUMBER OF POLES	Three-pole
OPERATING TEMPERATURE - MAX	120 °C
OPERATING TEMPERATURE - MIN	120 °C
WIRE SIZE	Load: #8-16 AWG Cu Load: (2)#12-16 AWG Cu Line: #6 AWG Cu Line: (2) #10 AWG Cu

Resources

	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
CATALOGS	Bussmann series complete full line catalog no. 1007 JM60060-3MW24-FUSE BLK, J 600V 60A 3P
CERTIFICATION REPORTS	Eaton Bussmann EU Declaration of conformity 93-68-EEC2201
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - JM60060-3MW24

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.