



355 CONCRETE INSERT, EG

CATALOG NUMBER

3550000EG



CERTIFICATIONS



FEATURES

Structural attachment in all grades of concrete

Knockout keeps interior empty during pour

Allows for horizontal rod adjustment up to 1-1/4"

355N Insert Nut required for UL Listing and FM Approval

Conforms with Federal Specification WW-H-171 (Type 19), Manufacturers Standardization Society ANSI®/MSS-SP-58 (Type 18)

PRODUCT ATTRIBUTES

Material: Steel

Finish: Electrogalvanized

Rod Size: 3/8";1/2";5/8";3/4";7/8"

A: 1 5/8"

B: 3 9/16"

C: 3"

Pipe Size: 10" Max

Static Load: 1,200 lb

ADDITIONAL PRODUCT DETAILS

Rod should be threaded through the nut until it tightens against the top of the insert.


For installation, place knockout side down on concrete form and nail in place. Wire 12" piece of #4 reinforcing rod on both sides. After concrete pour, knockout can be removed with a screwdriver.

cULus® Listed for 3/8" rod size up to 4" pipe and 1/2", 5/8" and 3/4" rod sizes up to 6" pipe.

FM® Approved for 3/8", 1/2", 5/8", and 3/4" rod sizes up to 8" pipe.

Install in accordance with applicable code.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com **CADDY ERICO HOFFMAN RAYCHEM SCHROFF**
TRACER