



Materials & Finishes - Standard:

- **Base Metal:** Steel conforms to ASTM A1011 SS GR 33, A1011 HSLAS GR 45, A36, A575, A576, or A635.
- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Power-Strut Defender (DF):** Conforms to ASTM A1059
- **Hot Dip Galvanized (HG):** Conforms to ASTM A123 or A153
- **Perma-Green (GR):** Conforms to commercial standards for powder coating
- **Perma-Gold (ZD):** Conforms to ASTM B633, Type II SC1
- **Plain (PL):** No finish

Materials & Finishes - Special Metals:

- **Stainless Steel, Type 304 (SS):** Conforms to ASTM A240 or A276, Type 304 *
- **Stainless Steel, Type 316 (ST):** Conforms to ASTM A240 or A276, Type 316 *
- **Aluminum (AL):** Conforms to ASTM B209, Type 1100F or 5052-H32 *

* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

Part No.	A	B	Finish	Product Weight / Piece (lbs)
PS 624 37-12°	37-1/2°	3" (76)	EG	0.58
PS 624 45°	45°	3-1/8" (79)	EG	0.58
PS 624 45°	45°	3-1/8" (79)	DF	0.615
PS 624 45°	45°	3-1/8" (79)	HG	0.615
PS 624 45°	45°	3-1/8" (79)	GR	0.58
PS 624 52-12°	52-1/2°	3-1/16" (78)	EG	0.58
PS 624 60°	60°	3-1/8" (79)	EG	0.58
PS 624 60°	60°	3-1/8" (79)	HG	0.615
PS 624 60°	60°	3-1/8" (79)	GR	0.58
PS 624 67-12°	67-1/2°	3-1/8" (79)	EG	0.58
PS 624 75°	75°	3-3/16" (81)	EG	0.58
PS 624 82-12°	82-1/2°	3-3/16" (81)	EG	0.58

Project:	<input style="width: 100%;" type="text"/>		
Architect / Engineer:	<input style="width: 100%;" type="text"/>		
Date:	<input style="width: 25%;" type="text"/>	Phone:	<input style="width: 50%;" type="text"/>
Contractor:	<input style="width: 100%;" type="text"/>		
Address:	<input style="width: 100%;" type="text"/>		
Notes:	<input style="width: 100%; height: 40px;" type="text"/>		

Approval Stamp: