



**Materials & Finishes - Standard:**

- **Base Metal:** Steel conforms to ASTM A1011 SS GR 33, A1011 HSLAS GR 45, A36, A575, A576, or A635.
- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Power-Strut Defender (DF):** Conforms to ASTM A1059
- **Hot Dip Galvanized (HG):** Conforms to ASTM A123 or A153
- **Perma-Green (GR):** Conforms to commercial standards for powder coating
- **Perma-Gold (ZD):** Conforms to ASTM B633, Type II SC1
- **Plain (PL):** No finish

**Materials & Finishes - Special Metals:**

- **Stainless Steel, Type 304 (SS):** Conforms to ASTM A240 or A276, Type 304 \*
- **Stainless Steel, Type 316 (ST):** Conforms to ASTM A240 or A276, Type 316 \*
- **Aluminum (AL):** Conforms to ASTM B209, Type 1100F or 5052-H32 \*

\* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

Part No.	A	B	C	Finish	Product Weight / Piece (lbs)
PS 633 15°	15°	3-5/16" (84.1)	2-1/16"	EG	0.58
PS 633 22-1/2°	22-1/2°	3-5/16" (84.1)	2-1/16"	EG	0.58
PS 633 30°	30°	3-1/4" (82.6)	2-1/16"	EG	0.58
PS 633 30°	30°	3-1/4" (82.6)	2-1/16"	HG	0.615
PS 633 30°	30°	3-1/4" (82.6)	2-1/16"	GR	0.58
PS 633 30°	30°	3-1/4" (82.6)	2-1/16"	SS	0.58
PS 633 37-1/2°	37-1/2°	2-11/16"	2-5/8"	EG	0.58
PS 633 45°	45°	3" (76)	2-5/16" (59)	EG	0.58
PS 633 45°	45°	3" (76)	2-5/16" (59)	DF	0.615
PS 633 45°	45°	3" (76)	2-5/16" (59)	HG	0.615
PS 633 45°	45°	3" (76)	2-5/16" (59)	GR	0.58
PS 633 45°	45°	3" (76)	2-5/16" (59)	SS	0.58
PS 633 45°	45°	3" (76)	2-5/16" (59)	AL	0.23
PS 633 52-1/2°	52-1/2°	3-1/4"	2-1/16"	EG	0.58
PS 633 60°	60°	3-3/8"	1-7/8"	EG	0.58
PS 633 60°	60°	3-3/8"	1-7/8"	HG	0.615
PS 633 60°	60°	3-3/8"	1-7/8"	GR	0.58
PS 633 60°	60°	3-3/8"	1-7/8"	SS	0.58
PS 633 67-1/2°	67-1/2°	3-1/2"	1-3/4"	EG	0.58
PS 633 7-1/2°	7-1/2°	3-5/16" (84.1)	2-1/16"	EG	0.55
PS 633 75°	75°	3-9/16"	1-11/16"	EG	0.58
PS 633 82-1/2°	82-1/2°	3-9/16"	1-11/16"	EG	0.58

**Project:**

**Architect / Engineer:**

**Date:**  **Phone:**

**Contractor:**

**Address:**

**Notes:**

**Approval Stamp:**