



Materials & Finishes - Standard:

- **Base Metal:** Steel conforms to ASTM A1011 SS GR 33, A1011 HSLAS GR 45, A36, A575, A576, or A635.
- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Power-Strut Defender (DF):** Conforms to ASTM A1059
- **Hot Dip Galvanized (HG):** Conforms to ASTM A123 or A153
- **Perma-Green (GR):** Conforms to commercial standards for powder coating
- **Perma-Gold (ZD):** Conforms to ASTM B633, Type II SC1
- **Plain (PL):** No finish

Materials & Finishes - Special Metals:

- **Stainless Steel, Type 304 (SS):** Conforms to ASTM A240 or A276, Type 304 *
- **Stainless Steel, Type 316 (ST):** Conforms to ASTM A240 or A276, Type 316 *
- **Aluminum (AL):** Conforms to ASTM B209, Type 1100F or 5052-H32 *

* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

Part No.	A	Finish	Product Weight / Piece (lbs)
PS 808 T1-06	6" (152.4)	HG	1.707
PS 808 T1-06	6" (152.4)	GR	1.61
PS 808 T1-06	6" (152.4)	SS	1.61
PS 808 T1-12	12" (304.8)	HG	2.767
PS 808 T1-12	12" (304.8)	GR	2.61
PS 808 T1-12	12" (304.8)	SS	2.61
PS 808 T1-18	18" (457.2)	HG	3.827
PS 808 T1-18	18" (457.2)	GR	3.61
PS 808 T1-18	18" (457.2)	SS	3.61
PS 808 T1-24	24" (609.6)	HG	4.887
PS 808 T1-24	24" (609.6)	GR	4.61
PS 808 T1-24	24" (609.6)	SS	4.61

Project:	<input style="width: 100%;" type="text"/>		
Architect / Engineer:	<input style="width: 100%;" type="text"/>		
Date:	<input style="width: 25%;" type="text"/>	Phone:	<input style="width: 50%;" type="text"/>
Contractor:	<input style="width: 100%;" type="text"/>		
Address:	<input style="width: 100%;" type="text"/>		
Notes:	<input style="width: 100%;" type="text"/>		

Approval Stamp: