



Representative

**Catalog Number:** FBB18-1  
**Product ID:** 7TAA014910R0051  
**UPC Number:** 78378640977  
**Status:** Active

Flexible Braids for Grounding, 24000 Circular Mil Area, Bolt Hole 1/4, 18 inch length, Number of Braids in Ferrule 1, 1 Bolt Hole in Ferrule

### UNSPSC Specifications

UNSPSC	39121465 Flexible braid
IGCC	4695 Flexible braid
Brand Name	Blackburn
Type	Flexible Braid
Special Features	Tin-Plated Copper Braids and Ferrules for High Conductivity and Corrosion Resistance. Enables Linear Expansion, Equipment Vibration and Offset Connections.
Application	Flexible Copper Braids for use in Substation and Grounding Applications
Standard	Certified C22.2 No. 41 Grounding and Bonding Equipment, Listed UL467 and UL486A Grounding and Bonding Equipment.
Conductor Material	Tin-Plated Copper
Nominal Cross Section Conductor	24000 Circular Mils
Cable Width	.625 inch
Cable Length	18 inch
Conductor Category	Flexible
Shape Of Conductor	Flat

### Packaging

Outer Quantity	50
Outer Dimensions (inches)	18x5.5x4
Weight Uom	10 lbs. per 100

### Documents / Support Tools

Technical Data Sheet CA	Available on Website
-------------------------	----------------------

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
 www.tnb.com

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email:techsupport@tnb.com