

Catalog Number: PAFL21/BL/50M
Product ID: 7TCA296000R2125
EAN Number: 05020963010118
Status: Active

Lightweight Conduit, Nominal Conduit Size 21mm, NW Conduit Size 17, Fine Conduit Pitch, Outside Diameter 21.2mm, Inside Diameter 16.8mm, Static Bend Radius 45mm, Reel Length 50 Meters, Polyamide (Nylon) 6, Black



Actual

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5535 Electrical conduit
Brand Name	Adaptaflex
Type	Lightweight Conduit with Fine Pitch
Special Features	Very High UV Protection and Fatigue Life
Application	Indoors / Outdoors - Light Industrial, Buildings & Machinery
Trade Size	21mm
Outside Diameter	21.2mm
Inside Diameter	16.8mm
Length	50 m
Radius	45mm
Flexibility	High
Material	Polyamide/Nylon 6
Color	Black

European Specifications (ETIM)

ETIM	EC001175 Corrugated plastic hose
Nominal diameter	21mm
Outer diameter	21.2mm
Inner diameter	16.8mm
Material	Polyamide 6
Operating temperature	-40-+120°C
Degree of protection (IP)	IP68
Fire resistance in accordance with UL94	HB
UV resistant	Y
Colour	Black
Sheathing material	Not sheathed
Bending strength	Flexible
Lengthwise slotted	N
Halogen free	Y
Approved according to DIN EN 61386-23	Y
Approved according to LUL/British Standard	Y
Approved according to Lloyd's Register TA	Y

Packaging

Inner Quantity	1
Inner Dimensions (inches)	17x17x17
Outer Quantity	1
Outer Dimensions (inches)	17x37x17
Weight Uom	6.17 lbs. Each

For further technical assistance, please contact us...

Memphis, TN 38120
www.tnb.com

860 Ridge Lake Blvd.
Memphis, TN 38120

Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com