



Representative

Catalog Number: SDK-M
Product ID: 7TAA260520R0047
UPC Number: 78378675146
Status: Active

Flood-Seal Street and Highway Lighting Mechanical Fuse and Disconnect Kits-In-Line, non-fused, conductor range stranded 12,10,8,6,4 and solid 12,10,8,6,4

North American Specifications (UNSPSC)

UNSPSC	39121421 Electrical connector assembly
IGCC	4586 Electrical connector assembly
Brand Name	Homac
Type	Flood-Seal Street and Highway Lighting Mechanical Fuse an Disconnect Kit - In Line
Special Features	EPDM Rubber housing ensures a fully insulated, watertight and submersible connection. Safe separations - fuse or connecting link stays in load side when separated. Dual-rated and approved for a wide range of Aluminum or Copper Conductors.
Application	Rated for 600 Colts, 30 Amps Maximum - perfect for Heavy duty applications
Connection	Mechanical
Conductor Range	12, 10, 8, 6 and 4 Stranded and Solid
Number Of Conductors	2
Material	EPDM Rubber Housing
Insulation	Yes

Packaging

Outer Quantity	25
Outer Dimensions (inches)	12x6.25x9.25
Weight Uom	17.5 lbs. per 100

Documents / Support Tools

SDS US 1	sds-00048-tb2
Technical Data Sheet CA	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com